

BATTERY MODEL: 12.8V 36AH LIFEPO4

Description	Technical Specification	Remark
Nominal Capacity	36Ah	Capacity according to standard charge and Discharge
Nominal Voltage	12.8V	The average value of working voltage during the whole discharge process.
Nominal Wattage	461Wh	
Internal Impedance of Pack	≤5.3mΩ	Internal Impedance calculated after series and parallel configuration
Type of Cell	Cylindrical	Part No. 32650
Capacity of Individual Cell	3.2V – 6000mAh	A Grade Cell with IR < 8mΩ
Configuration	4S-6P	4 in Series and 6 in Parallel
Charge Current	5-8A	Constant Charge
Discharge Current	8A	Constant Discharge
Charge Cut-Off Voltage	14.6V	Protected with Balancing BMS
Discharge Cut-Off Voltage	10.5V	Protected with Balancing BMS
Working Temperature (Charging)	0-45°C	Under constant charge
Working Temperature (Discharging)	20-55°C	Under constant discharge
Weight	3.84kG	Approx
Dimension	Length (mm)	200mm
	Width (mm)	130mm
	Height (mm)	70mm
Cycle Life	≥2000	With 80% DOD
Storage Temperature	1 – 3 Month	20 - 60°C
	1 – 6 Month	20 - 45°C
Battery (LCV)	Provided	
Battery (HCV)	Provided	
Battery Reverse Protection	Provided	